



LIGHT DUTY V-BELTS

Truflex® V-Belts

Truflex belts feature superior length stability for minimal take-up requirements.

Markets/Applications

Suitable for all industrial light duty applications, usually using fractional horsepower (FHP) motors.

Features/Advantages


- **Gates Curves** provide proper cord support and full contact with the sheave-groove for uniform loading, uniform wear, and increased belt life.
- **Flex-Bonded Cords** are strongly bonded to the body of the belt resulting in equal load distribution and the absorption of bending stress without cord deterioration.
- **The Flex-Weave® Cover** is a patented construction for longer cover life, providing extended protection to the core of the belt from oil, dirt, and heat.
- Meets RMA **oil and heat resistant** standards.
- Meets RMA **static conductivity** requirements.

Recommended Sheaves

Light-Duty Sheaves-Bored-to-Size
Light-Duty Sheaves-Variable Pitch
Light-Duty Sheaves-Bushed


Notes

Truflex belts are offered in cross sections 2L (0), 3L (1), 4L (2), 5L (3).



Product No. Series 8400


0 or 2L Section



Part No.	Industry No.	Product No.	Belt O.C. (In.)	Wt. Ea. (Lbs.)	Customer Pack
0100	2L100	8400-0100	10.0	.01	1
0110	2L110	8400-0110	11.0	.01	1
0120	2L120	8400-0120	12.0	.02	1
0130	2L130	8400-0130	13.0	.02	1
0140	2L140	8400-0140	14.0	.02	1
0150	2L150	8400-0150	15.0	.02	1
0160	2L160	8400-0160	16.0	.02	1
0170	2L170	8400-0170	17.0	.02	1
0180	2L180	8400-0180	18.0	.02	1
0190	2L190	8400-0190	19.0	.02	1
0200	2L200	8400-0200	20.0	.03	1
0210	2L210	8400-0210	21.0	.03	1
0230	2L230	8400-0230	23.0	.03	1

Part No.	Industry No.	Product No.	Belt O.C. (In.)	Wt. Ea. (Lbs.)	Customer Pack
0240	2L240	8400-0240	24.0	.03	1
0250	2L250	8400-0250	25.0	.02	1
0260	2L260	8400-0260	26.0	.04	1
0270	2L270	8400-0270	27.0	.04	1
0280	2L280	8400-0280	28.0	.04	1
0290	2L290	8400-0290	29.0	.04	1
0310	2L310	8400-0310	31.0	.04	1
0340	2L340	8400-0340	34.0	.05	1
0350	2L350	8400-0350	35.0	.05	1
0360	2L360	8400-0360	36.0	.05	1
0380	2L380	8400-0380	38.0	.05	1
0460	2L460	8400-0460	46.0	.07	1

1 or 3L Section



Part No.	Industry No.	Product No.	Belt O.C. (In.)	Wt. Ea. (Lbs.)	Customer Pack
1110	3L110	8400-1110	11.0	.05	1
1120	3L120	8400-1120	12.0	.06	1
1130	3L130	8400-1130	13.0	.06	1
1140	3L140	8400-1140	14.0	.06	1
1150	3L150	8400-1150	15.0	.06	1
1160	3L160	8400-1160	16.0	.07	1
1170	3L170	8400-1170	17.0	.07	1
1180	3L180	8400-1180	18.0	.07	1
1190	3L190	8400-1190	19.0	.07	1
1200	3L200	8400-1200	20.0	.08	1
1210	3L210	8400-1210	21.0	.07	1

Part No.	Industry No.	Product No.	Belt O.C. (In.)	Wt. Ea. (Lbs.)	Customer Pack
1220	3L220	8400-1220	22.0	.08	1
1230	3L230	8400-1230	23.0	.08	1
1240	3L240	8400-1240	24.0	.10	1
1245	3L245	8400-1245	24.5	.09	1
1250	3L250	8400-1250	25.0	.09	1
1255	3L255	8400-1255	25.5	.09	1
1260	3L260	8400-1260	26.0	.09	1
1265	3L265	8400-1265	26.5	.09	1
1270	3L270	8400-1270	27.0	.09	1
1275	3L275	8400-1275	27.5	.09	1
1280	3L280	8400-1280	28.0	.09	1



Truflex® V-Belts

Product No. Series 8400 (continued)


1 or 3L Section (continued)

Part No.	Industry No.	Product No.	Belt O.C. (In.)	Wt. Ea. (Lbs.)	Customer Pack
1285	3L285	8400-1285	28.5	.10	1
1290	3L290	8400-1290	29.0	.10	1
1293	3L293	8400-1293	29.2	.10	1
1300	3L300	8400-1300	30.0	.10	1
1310	3L310	8400-1310	31.0	.10	1
1320	3L320	8400-1320	32.0	.11	1
1330	3L330	8400-1330	33.0	.11	1
1340	3L340	8400-1340	34.0	.11	1
1345	3L345	8400-1345	34.2	.11	1
1350	3L350	8400-1350	35.0	.11	1
1360	3L360	8400-1360	36.0	.11	1
1370	3L370	8400-1370	37.0	.12	1
1380	3L380	8400-1380	38.0	.12	1
1390	3L390	8400-1390	39.0	.12	1
1400	3L400	8400-1400	40.0	.13	1
1410	3L410	8400-1410	41.0	.13	1
1415	3L415	8400-1415	41.5	.13	1
1420	3L420	8400-1420	42.0	.13	1
1430	3L430	8400-1430	43.0	.13	1
1440	3L440	8400-1440	44.0	.14	1
1450	3L450	8400-1450	45.0	.14	1
1460	3L460	8400-1460	46.0	.14	1
1470	3L470	8400-1470	47.0	.14	1
1480	3L480	8400-1480	48.0	.15	1
1490	3L490	8400-1490	49.0	.15	1

Part No.	Industry No.	Product No.	Belt O.C. (In.)	Wt. Ea. (Lbs.)	Customer Pack
1500	3L500	8400-1500	50.0	.15	1
1510	3L510	8400-1510	51.0	.15	1
1520	3L520	8400-1520	52.0	.15	1
1530	3L530	8400-1530	53.0	.16	1
1540	3L540	8400-1540	54.0	.16	1
1550	3L550	8400-1550	55.0	.16	1
1560	3L560	8400-1560	56.0	.16	1
1570	3L570	8400-1570	57.0	.17	1
1580	3L580	8400-1580	58.0	.17	1
1590	3L590	8400-1590	59.0	.17	1
1600	3L600	8400-1600	60.0	.17	1
1610	3L610	8400-1610	61.0	.18	1
1620	3L620	8400-1620	62.0	.18	1
1630	3L630	8400-1630	63.0	.18	1
1640	3L640	8400-1640	64.0	.18	1
1650	3L650	8400-1650	65.0	.19	1
1660	3L660	8400-1660	66.0	.19	1
1670	3L670	8400-1670	67.0	.19	1
1675	3L675	8400-1675	67.5	.19	1
1680	3L680	8400-1680	68.0	.19	1
1690	3L690	8400-1690	69.0	.20	1
1700	3L700	8400-1700	70.0	.20	1
1710	3L710	8400-1710	71.0	.20	1
1730	3L730	8400-1730	73.0	.21	1
1740	3L740	8400-1740	74.0	.21	1

2 or 4L Section

Part No.	Industry No.	Product No.	Belt O.C. (In.)	Wt. Ea. (Lbs.)	Customer Pack
2150	4L150	8400-2150	15.0	.08	1
2160	4L160	8400-2160	16.0	.07	1
2170	4L170	8400-2170	17.0	.09	1
2180	4L180	8400-2180	18.0	.10	1
2188	4L188	8400-2188	18.7	.10	1
2190	4L190	8400-2190	19.0	.11	1
2200	4L200	8400-2200	20.0	.11	1
2210	4L210	8400-2210	21.0	.11	1
2215	4L215	8400-2215	21.5	.11	1
2220	4L220	8400-2220	22.0	.12	1
2230	4L230	8400-2230	23.0	.12	1
2235	4L235	8400-2235	23.5	.10	1
2240	4L240	8400-2240	24.0	.12	1
2250	4L250	8400-2250	25.0	.13	1
2255	4L255	8400-2255	25.5	.14	1
2260	4L260	8400-2260	26.0	.14	1
2270	4L270	8400-2270	27.0	.15	1
2275	4L275	8400-2275	27.5	.15	1
2280	4L280	8400-2280	28.0	.15	1
2285	4L285	8400-2285	28.5	.15	1
2290	4L290	8400-2290	29.0	.15	1
2295	4L295	8400-2295	29.5	.16	1
2300	4L300	8400-2300	30.0	.16	1
2310	4L310	8400-2310	31.0	.16	1
2318	4L318	8400-2318	31.7	.17	1
2320	4L320	8400-2320	32.0	.17	1
2328	4L328	8400-2328	32.7	.18	1
2330	4L330	8400-2330	33.0	.18	1
2333	4L333	8400-2333	33.2	.18	1



Part No.	Industry No.	Product No.	Belt O.C. (In.)	Wt. Ea. (Lbs.)	Customer Pack
2338	4L338	8400-2338	33.7	.18	1
2340	4L340	8400-2340	34.0	.19	1
2346	4L346	8400-2346	34.5	.19	1
2350	4L350	8400-2350	35.0	.19	1
2360	4L360	8400-2360	36.0	.20	1
2370	4L370	8400-2370	37.0	.20	1
2380	4L380	8400-2380	38.0	.20	1
2390	4L390	8400-2390	39.0	.21	1
2400	4L400	8400-2400	40.0	.21	1
2405	4L405	8400-2405	40.5	.21	1
2410	4L410	8400-2410	41.0	.22	1
2420	4L420	8400-2420	42.0	.22	1
2430	4L430	8400-2430	43.0	.23	1
2440	4L440	8400-2440	44.0	.23	1
2450	4L450	8400-2450	45.0	.24	1
2460	4L460	8400-2460	46.0	.24	1
2470	4L470	8400-2470	47.0	.25	1
2475	4L475	8400-2475	47.5	.25	1
2480	4L480	8400-2480	48.0	.25	1
2490	4L490	8400-2490	49.0	.26	1
2500	4L500	8400-2500	50.0	.26	1
2510	4L510	8400-2510	51.0	.27	1
2520	4L520	8400-2520	52.0	.28	1
2530	4L530	8400-2530	53.0	.28	1
2540	4L540	8400-2540	54.0	.29	1
2550	4L550	8400-2550	55.0	.30	1
2560	4L560	8400-2560	56.0	.30	1
2570	4L570	8400-2570	57.0	.30	1
2580	4L580	8400-2580	58.0	.31	1

LIGHT DUTY V-BELTS






Truflex® V-Belts

Product No. Series 8400 (continued)

2 or 4L Section (continued)

Part No.	Industry No.	Product No.	Belt O.C. (In.)	Wt. Ea. (Lbs.)	Customer Pack
2590	4L590	8400-2590	59.0	.31	1
2600	4L600	8400-2600	60.0	.32	1
2610	4L610	8400-2610	61.0	.33	1
2620	4L620	8400-2620	62.0	.33	1
2630	4L630	8400-2630	63.0	.34	1
2640	4L640	8400-2640	64.0	.34	1
2650	4L650	8400-2650	65.0	.35	1
2660	4L660	8400-2660	66.0	.35	1
2670	4L670	8400-2670	67.0	.36	1
2680	4L680	8400-2680	68.0	.36	1
2690	4L690	8400-2690	69.0	.37	1
2700	4L700	8400-2700	70.0	.37	1
2710	4L710	8400-2710	71.0	.38	1
2720	4L720	8400-2720	72.0	.39	1
2730	4L730	8400-2730	73.0	.39	1
2740	4L740	8400-2740	74.0	.40	1
2750	4L750	8400-2750	75.0	.40	1
2760	4L760	8400-2760	76.0	.41	1
2770	4L770	8400-2770	77.0	.41	1
2780	4L780	8400-2780	78.0	.42	1
2790	4L790	8400-2790	79.0	.42	1

Part No.	Industry No.	Product No.	Belt O.C. (In.)	Wt. Ea. (Lbs.)	Customer Pack
2800	4L800	8400-2800	80.0	.43	1
2810	4L810	8400-2810	81.0	.44	1
2820	4L820	8400-2820	82.0	.44	1
2830	4L830	8400-2830	83.0	.45	1
2840	4L840	8400-2840	84.0	.45	1
2850	4L850	8400-2850	85.0	.46	1
2860	4L860	8400-2860	86.0	.46	1
2870	4L870	8400-2870	87.0	.47	1
2880	4L880	8400-2880	88.0	.47	1
2890	4L890	8400-2890	89.0	.48	1
2900	4L900	8400-2900	90.0	.48	1
2910	4L910	8400-2910	91.0	.49	1
2920	4L920	8400-2920	92.0	.50	1
2930	4L930	8400-2930	93.0	.50	1
2940	4L940	8400-2940	94.0	.50	1
2950	4L950	8400-2950	95.0	.51	1
2960	4L960	8400-2960	96.0	.51	1
2970	4L970	8400-2970	97.0	.52	1
2980	4L980	8400-2980	98.0	.53	1
2990	4L990	8400-2990	99.0	.53	1
21000	4L1000	8400-2100	100.0	.54	1



3 or 5L Section

Part No.	Industry No.	Product No.	Belt O.C. (In.)	Wt. Ea. (Lbs.)	Customer Pack
3230	5L230	8400-3230	23.0	.20	1
3240	5L240	8400-3240	24.0	.22	1
3250	5L250	8400-3250	25.0	.22	1
3260	5L260	8400-3260	26.0	.23	1
3265	5L265	8400-3265	26.5	.23	1
3270	5L270	8400-3270	27.0	.24	1
3280	5L280	8400-3280	28.0	.25	1
3290	5L290	8400-3290	29.0	.25	1
3300	5L300	8400-3300	30.0	.26	1
3310	5L310	8400-3310	31.0	.27	1
3320	5L320	8400-3320	32.0	.28	1
3330	5L330	8400-3330	33.0	.29	1
3340	5L340	8400-3340	34.0	.30	1
3350	5L350	8400-3350	35.0	.30	1
3355	5L355	8400-3355	35.5	.31	1
3360	5L360	8400-3360	36.0	.31	1
3370	5L370	8400-3370	37.0	.32	1
3380	5L380	8400-3380	38.0	.33	1
3390	5L390	8400-3390	39.0	.34	1
3400	5L400	8400-3400	40.0	.35	1
3410	5L410	8400-3410	41.0	.35	1
3420	5L420	8400-3420	42.0	.36	1
3430	5L430	8400-3430	43.0	.37	1
3440	5L440	8400-3440	44.0	.38	1
3450	5L450	8400-3450	45.0	.39	1
3460	5L460	8400-3460	46.0	.40	1
3470	5L470	8400-3470	47.0	.40	1
3480	5L480	8400-3480	48.0	.41	1
3490	5L490	8400-3490	49.0	.42	1
3500	5L500	8400-3500	50.0	.43	1
3510	5L510	8400-3510	51.0	.44	1
3520	5L520	8400-3520	52.0	.45	1

Part No.	Industry No.	Product No.	Belt O.C. (In.)	Wt. Ea. (Lbs.)	Customer Pack
3530	5L530	8400-3530	53.0	.45	1
3540	5L540	8400-3540	54.0	.46	1
3550	5L550	8400-3550	55.0	.47	1
3560	5L560	8400-3560	56.0	.48	1
3570	5L570	8400-3570	57.0	.49	1
3580	5L580	8400-3580	58.0	.49	1
3590	5L590	8400-3590	59.0	.50	1
3600	5L600	8400-3600	60.0	.51	1
3610	5L610	8400-3610	61.0	.52	1
3620	5L620	8400-3620	62.0	.53	1
3630	5L630	8400-3630	63.0	.54	1
3640	5L640	8400-3640	64.0	.55	1
3650	5L650	8400-3650	65.0	.55	1
3660	5L660	8400-3660	66.0	.56	1
3670	5L670	8400-3670	67.0	.57	1
3680	5L680	8400-3680	68.0	.58	1
3690	5L690	8400-3690	69.0	.59	1
3700	5L700	8400-3700	70.0	.60	1
3710	5L710	8400-3710	71.0	.60	1
3720	5L720	8400-3720	72.0	.61	1
3730	5L730	8400-3730	73.0	.62	1
3740	5L740	8400-3740	74.0	.62	1
3750	5L750	8400-3750	75.0	.63	1
3760	5L760	8400-3760	76.0	.64	1
3770	5L770	8400-3770	77.0	.65	1
3780	5L780	8400-3780	78.0	.66	1
3790	5L790	8400-3790	79.0	.67	1
3800	5L800	8400-3800	80.0	.67	1
3810	5L810	8400-3810	81.0	.68	1
3820	5L820	8400-3820	82.0	.69	1
3830	5L830	8400-3830	83.0	.70	1
3840	5L840	8400-3840	84.0	.71	1



Truflex® V-Belts**Product No. Series 8400 (continued)****3 or 5L Section (continued)**

Part No.	Industry No.	Product No.	Belt O.C. (In.)	Wt. Ea. (Lbs.)	Customer Pack
3850	5L850	8400-3850	85.0	.72	1
3860	5L860	8400-3860	86.0	.73	1
3870	5L870	8400-3870	87.0	.73	1
3880	5L880	8400-3880	88.0	.74	1
3890	5L890	8400-3890	89.0	.75	1
3900	5L900	8400-3900	90.0	.76	1
3910	5L910	8400-3910	91.0	.77	1
3920	5L920	8400-3920	92.0	.78	1

Part No.	Industry No.	Product No.	Belt O.C. (In.)	Wt. Ea. (Lbs.)	Customer Pack
3930	5L930	8400-3930	93.0	.78	1
3940	5L940	8400-3940	94.0	.79	1
3950	5L950	8400-3950	95.0	.80	1
3960	5L960	8400-3960	96.0	.81	1
3970	5L970	8400-3970	97.0	.81	1
3980	5L980	8400-3980	98.0	.82	1
3990	5L990	8400-3990	99.0	.83	1
3999	5L1000	8400-3100	100.0	.84	1